View NSN Online: https://aerobasegroup.kr/nsn/6750-01-474-2993

Product ID:8612-6M, MAGENTA TONER CONCENTRATE MSDS Date:01/01/2001 FSC:6750 NIIN:01-474-2993 Status Code:A Kit Part:Y **MSDS Number: CLQDK** === Responsible Party === Company Name: SPECIALTY TONER CORP Address:19 INDUSTRIAL ROAD City:FAIRFIELD State:NJ ZIP:07004 Country:US Info Phone Num:97 3-575-3643/ (973) 575-9626 FAX Emergency Phone Num: (202) 483-7616 Chemtrec Ind/Phone:(800)424-9300 CAGE:1PVH2 === Contractor Identification === Company Name: SPECIALTY TONER CORP Address:19 INDUSTRIAL ROAD Box:City:FAIRFIELD State:NJ ZIP:07004 Country:US Phone:973-575-3643/ (973) 575-9626 FAX CAGE:1PVH2

Ingred Name:POLYMER/RESIN NJTSRN# 222760362-5014

Ingred Name:POLYMER/RESIN NJTSRN# 222760362-5015 ACGIH TLV:NONE ESTABLISHED Ingred Name:(PIGMENT) RED NJTSRN# 222760362-5005 &It; Wt:6.

Ingred Name:ISOPARAFFINIC PETROLEUM SOLVENT CAS:64742-48-9 = Wt:84. ACGIH TLV:300 PPM

Ingred Name:POLYMER/RESIN NJSRN# 222760362-5013 &It; Wt:9. ACGIH TLV:NONE

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE: IRRITANT TO EYE - MAY CAUSE CONJUNCTIVITIS. SKIN: PROLONGED CONTACT CAUSES DEFATTING, DRYING, CRACKING DER

MATITIS. INHALATION: NOT NORMALLY AN INHALATION HAZARD, OVEREXPOSURE MAY CAUSE HEADACHE, NAUSEA AND RESPIRATORY IRRITATION. INGESTION: NAUSEA AND POSSIBLE GASTRO-INTESTINAL IRRITATION. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.

Effects of Overexposure:EYE: IRRITANT TO EYE - MAY CAUSE CONJUNCTIVITIS. SKIN: PROLONGED CONTACT CAUSES DEFATTING, DRYING, CRACKING DERMATITIS. INHALATION: NOT NORMALLY AN INHALATION HAZARD, OVEREXPOSURE MAY CAUSE HEADACHE, NAUSEA AND RESPIRA TORY

IRRITATION. INGESTION: NAUSEA AND POSSIBLE GASTRO-INTESTINAL IRRITATION. TARGET ORGANS: EYES, SKIN, RESPIRATORY SYSTEM.

Medical Cond Aggravated by Exposure:DERMATITIS. REPEATED INHALATION EXPOSURE TO RATE OF A SIMILAR HYDROCARBON AT CONCENTRATIONS GREATER THAN OR EQUAL TO 300PPM IN AIR CAUSED LOW GRADE (MILD) ANEMIA AND KIDNEY EFFECTS.

First Aid:EYE: FLUSH WITH LARGE AMOUNTS OF WATER, INCLUDING UNDER EYELIDS. SKIN: WASH WITH SOAP AND WATER. REMOVE ANY CONTAMINATED CLOTHING. INHALATION: MOVE TO FRESH AIR; IF BREATHING DIFFICULTY, ADMINISTER OX YGEN AND GET MEDICAL HELP. INGESTION: DO NOT INDUCE VOMITING DUE TO ASPIRATION HAZARD. CALL A PHYSICIAN.

Flash Point Method:TCC Flash Point:103-106F Autoignition Temp:=293.3C, 560.F Autoignition Temp Text:APPROX Lower Limits:0.8 Upper Limits:7.0 Extinguishing Media:FO

 AM, DRY CHEMICAL, CO2, WATER FOG. Fire Fighting Procedures: AVOID WATER, IT TENDS TO SPREAD HYDROCARBON FIRES. Unusual Fire/Explosion Hazard: (NFPA) HEALTH 1, FLAMMABILITY 2, REACTIVITY 0, RECOMMENDED BY EXXON.
======================================
Spill Release Procedures:REMOVE IGNITION SOURCES. COLLECT ON INERT ABSORBENT MATERIAL. PLACE IN WASTE CONTAINER APPROVED FOR COMBUSTIBLE WASTE.
======================================
Handling and Storage Precautions:STORE IN CLOSED, COOL, WELL-VENTILATED AREA AWAY FROM HEAT AND FLAME. Other Precautions:READ AND FOLLOW LABEL PRECAUTIONS. DO NOT REUSE CONTAINER.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:NOT REQUIRED. Ventilation:LOCAL EXHAUST: TO MAINTAIN BELOW TLV. Protective Gloves:LATEX GLOVES FOR OVEREXPOSURE. Eye Protection:GOGGLES FOR POSSIBLE SPLASHING. Other Protective Equipment:AN EYEWASH STATION IS D ESIRABLE IF SPLASHING IS A POSSIBILITY. Supplemental Safety and Health ITEM IS PART OF A KIT. SEE MSDS SERIAL# CLQDW,CLQDV, CLQDT, CLQDS, CLQDR, CLQDQ, CLQDP, CLQDN, CLQDM, CLQDL, CLQDX, AND CLQDJ.
======================================
HCC:F4 Boiling Pt:B.P. Text:160-180C Vapor Pres:1 MM @68F Vapor Density:5 Spec Gravity:0.76 Evaporation Rate & amp; Reference:.2545 Solubility in Water:IMMISCIBLE Appearance and Odor:RED/SLIGHT.
============== Stabi

lity and Reactivity Data ============

Stability Indicator/Materials to Avoid:YES VERY STRONG OXIDANTS LIKE CHROMIC ACID OR LIQUID CHLORINE. Stability Condition to Avoid:NONE Hazardous Decomposition Products:NONE Conditions to Avoid Polymerization:WILL NOT OCCUR.

Toxicological Information: (THIS MATERIAL HAS BEEN EXTENSIVELY TESTED. WHEN USED AS INTENDED, IT DOES NOT REPRESENT ANY KNOWN HEALTH OR SAFETY HAZARD.) OR

AL LD50: 5 G/KG(RAT) *INFORMATION SUPPLIED BY EXXON. *RECOMMENDED EXPOSUR E LIMIT 300PPM FOR SOLVENT MANUFACTURED BY EXXON. DERMAL LD50: 3.16 G/KG(RABBIT). INHALATION LD50: N/A. TLV: N/A. PEL: N/A. VOLATILE N/A (WGT.) 80-100%.

Ecological: AQUATIC LD50: N/A.

Waste Disposal Methods:TREAT AS HAZARDOUS WASTE AND DISPOSE IN ACCORDANCE WITH LOCAL E NVIRONMENTAL REGULATIONS. DO NOT POUR DOWN COMMON DRAIN.

- Transport Information:IMDG (I.E. OCEAN) PROPER SHIPPING NAME: PETROLEUM DISTILLATES, N.O.S. (CONTAINS ALIPHATIC HYDROCARBON LIQUID, RESIN PIGMENT). FLAMMABLE LIQUID, HAZARD CLASSIFICATION: 3.3 ID NUMBER: UN1268. PACKING GR OUP III, IMDG PAGE #3375. IATA PROPER SHIPPING NAME: PETROLEUM DISTILLATE, N.O.S., CONTAINS ALIPHATIC HYDROCARBON LIQUID, RES
- IN, PIGMENT). FLAMMABLE LIQUID, HAZARD CLASSIFICATION: 3 ID NUMBER: UN1268. PACKING GROUP III. DOT PROPER SHIPPING NAME: COMBUSTIBLE LIQUID, N.O.S., (CONTAINS ALIPHATIC HYDROCARBON LIQUID, RESIN, PIGMENT), NA 1993, PG III HAZARD CLASSIFICATION: COMB. LIQUID.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.