

UNION CARBIDE CORP LINDE DIV -- ISOPROPANOL ANHYDROUS -- 6810-00-543-7915

===== Product Identification =====

Product ID:ISOPROPANOL ANHYDROUS

MSDS Date:08/10/1998

FSC:6810

NIIN:00-543-7915

Status Code:A

MSDS Number: CLQPV

=== Responsible Party ===

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Info Phone Num:800-822-4357; 3

04-744-3487

Emergency Phone Num:800-822-4357

Resp. Party Other MSDS Num.:000000001194

Preparer's Name:NOT PROVIDED

CAGE:36346

=== Contractor Identification ===

Company Name:P AND D CREATIVE CO, INC

Address:20140 SCHOLAR DR SUITE 211

Box:City:HAGERSTOWN

State:MD

ZIP:21742

Country:US

Phone:301-797-3503

Contract Num:SP0450-02-M-M051

CAGE:1CVB1

Company Name:UNION CARBIDE CORP LINDE DIV

Address:39 OLD RIDGEBURY RD

Box:City:DANBURY

State:CT

ZIP:06817-0001

Country:US

Phone:800-822-4357; 304-744-3487

CAGE:36346

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROPANOL  
CAS:67-63-0  
RTECS #:NT8050000  
= Wt:100.  
Other REC Limits:NOT PROVIDED  
OSHA PEL:980 MG/M3;400 PPM  
ACGIH TLV:983 MG/M3;400 PPM  
ACGIH STEL:1230 MG/M3;500 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:NOT PROVIDED  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:ACUTE:INHALATION: HIGH CONCENTRATIONS  
OF VAPOR  
MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION, WITH LOSS OF  
CONSCIOUSNESS. VAPOR CAUSES IRRITATION OF RESPIRATORY TRACT. EYE  
CONTACT: CAUSES IRRITATION, CORNEAL INJURY. SKIN CONTACT: MAY  
CAUSE MINOR IRRITATION. PROLONGED OR REPEATED CONTACT MAY CAUSE  
DEFATTING AND DRYING OF SKIN. SKIN ABSORPTION: EXPOSURE TO SMALL  
QUANTITIES IS NOT EXPECTED TO CAUSE ADVERSE HEALTH EFFECTS.  
PROLONGED EXPOSURE MAY RESULT IN ABSORPTION OF HARMFUL AMOUNTS,  
PARTICULARLY IN INFANTS. SWALLOWING: SLIGHTLY TOXIC. MAY CAUSE  
DIZZINESS. CHRONIC: PROLONGED OR REPEATED SKIN EXPOSURE CAN CAUSE  
DEFATTING.  
Explanation of Carcinogenicity:NO EVIDENCE SUGGESTIVE OF CARCINOGENIC  
ACTIVITY WAS NOTED IN CHRONIC VAPOR INHALATION STUDIES WITH  
ISOPROPANOL IN RATS AND MICE.  
Effects of Overexposure:INHALATION: CNS DEPRESSION, WEAKNESS,  
DROWSINESS, LOSS OF CONSCIOUSNESS, RESPIRATORY TRACT IRRITATION,  
COUGHING, CHEST DISCOMFORT. EYE CONTACT: IRRITATION, STINGING,  
DISCOMFORT,  
PAIN, CORNEAL INJURY. SKIN CONTACT: IRRITATION,  
ITCHING, REDNESS, DEFATTING, DRYING. SKIN ABSORPTION: ADVERSE  
HEALTH EFFECTS, SAME SIGNS AS FOR INGESTION. INGESTION: DIZZINESS,  
FAINTNESS, DROWSINESS, DECREASED AWARENESS AND RESPONSIVENESS,  
LACK OF COORDINATION, ABDOMINAL DISCOMFORT, NAUSEA, VOMITING,  
DIARRHEA.  
Medical Cond Aggravated by Exposure:SKIN CONTACT MAY AGGRAVATE AN  
EXISTING DERMATITIS.

===== First Aid Measures =====

Firs

First Aid: INHALATION: MOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. IF BREATHING DIFFICULT, GIVE OXYGEN BY QUALIFIED PERSONNEL. GET MEDICAL ATTENTION. EYES: FLUSH WITH WATER, CONTINUE WASHING FOR SEVERAL MINUTES. REMOVE CONTACT LENSES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. IF IRRITATION PERSISTS OR IF CONTACT HAS BEEN PROLONGED, GET MEDICAL ATTENTION. SWALLOWING: IF PATIENT IS FULLY CONSCIOUS, GIVE TWO GLASSES OF WATER. INDUCE VOMITING. THIS SHOULD BE DONE ONLY BY MEDICAL OR EXPERIENCED FIRST-AID PERSONNEL. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point Method: TCC  
Flash Point: -11.7°C, 53°F  
Autoignition Temp: Autoignition Temp Text: N/A  
Lower Limits: 2.0  
Upper Limits: 12.7  
Extinguishing Media: APPLY ALCOHOL-TYPE OR ALL-PURPOSE-TYPE FOAM BY MANUFACTURER'S RECOMMENDED TECHNIQUES FOR LARGE FIRES. USE CARBON DIOXIDE OR DRY CHEMICAL MEDIA FOR SMALL FIRES.  
Fire Fighting Procedures: USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS AND STRUCTURES. USE WATER SPRAY TO DISPERSE VAPORS; RE-IGNITION IS POSSIBLE. USE SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard: PRODUCT VAPORS MAY TRAVEL OR BE MOVED BY AIR CURRENTS AND IGNITED BY PILOT LIGHTS, OTHER IGNITION SOURCES AT LOCATIONS DISTANT FROM PRODUCT HANDLING POINT. VAPORS FROM THIS MATERIAL MAY SETTLE IN LOW OR CONFINED AREAS OR TRAVEL A LONG DISTANCE TO AN IGNITION SOURCE AND FLASHBACK EXPLOSIVELY.

===== Accidental Release Measures =====

Spill Release Procedures: EXTINGUISH IGNITION SOURCE UNTIL AREA IS DETERMINED TO BE FREE FROM FIRE OR EXPLOSION HAZARD. SMALL SPILLS CAN BE FLUSHED WITH LARGE AMOUNTS OF WATER, LARGER SPILLS SHOULD BE COLLECTED FOR DISPOSAL. PERSONAL PRECAUTIONS: AVOID CONTACT WITH EYES. WEAR SUITABLE PROTECTIVE EQUIPMENT.  
Neutralizing

Agent:NOT RELEVANT

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS , FLAMES.  
AVOID CONTACT WITH EYES. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. VAPORS MAY TRAVEL OR MOVED BY AIR CURRENTS AND IGNITED BY PILOT LIGHTS, OTHER IGNIT ION SOURCES DISTANT FROM HANDLING POINT AND FLASHBACK EXPLOSIVELY. WASH THOROUGHLY AFTER HANDLING.  
Other Precautions:VAPOR MAY SETTLE IN LOW OR CONFINED AREAS, OR TRAVEL  
A LONG DISTANCE TO AN IGNITION SOURCE AND FLASH BACK EXPLOSIVELY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS IN HIGH VAPOR CONCENTRATIONS.  
Ventilation:GENERAL (MECHANICAL) ROOM VENTIALTION SHOULD BE SATISFACTORY. SPECIAL, LOCAL VENTILATION IS NEEDED AT POINTS WHERE VAPORS ESCAPE TO WORKPLACE AIR.  
Protective Gloves:PLASTIC, RUBBER.  
Eye Protection:MONOGOGGLES.  
Other Protective Equipme nt:EYE BATH, SAFETY SHOWER.  
Work Hygienic Practices:NOT PROVIDED  
Supplemental Safety and Health  
ABBREVIATION: N/A = NOT APPLICABLE. N/AV = NOT AVAILABLE. N/K = UNKNOWN. N/P = NOT PROVIDED. N/R = NOT RELEVANT. N/D = NOT DETERMINED. N/E = NOT ESTABLISHED. CNS = CENTRAL NERVOUS SYSTEM. GI = GASTROI NTESTINAL. SCBA = SELF CONTAINED BREATHING APPARATUS.

===== Physical/Chemical Properties =====

HCC:F2  
NRC/State Lic Num:NOT RELEVANT  
Boiling Pt:=82.3C, 180.1F  
Me  
It/Freeze Pt:=-88.3C, -127.F  
Decomp Temp:Decomp Text:NOT PROVIDED  
Vapor Pres:33 @ 20C/68F  
Vapor Density:2.1  
Spec Gravity:0.787 (H2O=1) 20C/20C  
VOC Pounds/Gallon:785  
Viscosity:NOT PROVIDED  
Evaporation Rate & Reference:2.9 (BUTYL ACETATE=1)  
Solubility in Water:100% @ 20C  
Appearance and Odor:TRANSPARENT COLORLESS LIQUID, SLIGHT ETHANOL/ACETONE-LIKE ODOR  
Percent Volatiles by Volume:100  
Corrosion Rate:NOT PROVIDED

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS. HALOGENS. STRONG INORGANIC ACIDS. ALDEHYDES.  
HALOGEN COMPOUNDS.

Stability Condition to Avoid: NOT PROVIDED

Hazardous Decomposition Products: CARBON MONOXIDE AND/OR CARBON DIOXIDE.  
CARBON MONOXIDE IS HIGHLY TOXIC IF INHALED; CARBON DIOXIDE IN  
SUFFICIENT CONCENTRATIONS CAN ACT AS AN ASPHYXANT.

===== Toxicological Information =====

Toxicological Information: ACUTE TOXICITY: PERORAL: RAT, LD50: 6.48

(4.80-8.76) ML/KG. MAJOR SIGNS: UNSTEADY GAIT, PROSTRATION, HEAVY  
BREATHING. GROSS PATHOLOGY: LUNGS AND ABDOMINAL VISCERA DISCOLORED.  
PERCUTANEOUS: RABBIT LD50 24 HR OCCLUDED 8.0 (4.9-13.1 ML/KG.  
GROSS PATHOLOGY: LUNGS, LIVER, STOMACH DISCOLORED. INHALATION:  
STATIC GENERATION OF VAPOR EXPOSURE TIME 2 H, RABBIT, ROOM  
TEMPERATURE, KILL RATE: 4/6, MAJOR SIGNS: LACRIMATION, LOSS OF  
COORDINATION, PROSTRATION. GROSS PATHOLOGY: LUNGS DISCOLORED.

===== Ecologi  
cal Information =====

Ecological: ENVIRONMENTAL FATE: BOD (% OXYGEN CONSUMPTION): DAY 5=28%;  
DAY 10=77%; DAY 20=78%. ECOTOXICITY TO MICRO-ORGANISMS: BACTERIAL/NA  
IC50 5000 MG/L. ECOTOXICITY TO AQUATIC INVERTEBRATES: DAPHNIA LC50  
48 H 7550 MG/L. ECOTOXICITY TO FISH: FATHEAD MINNOW LC50 96 H 8300  
MG/L. FURTHER INFORMATION: TI IOD (MEASURED) 2.30 MG/MG. TI IOD  
(CALCULATED) 2.40 MG/MG. OCTANOL/WATER PARTITION  
COEFFICIENT-MEASURED: 0.14.

===== D  
isposal Considerations =====

Waste Disposal Methods: INCINERATE IN FURNACE IF PERMITTED UNDER  
FEDERAL, STATE, LOCAL REGULATIONS. DISPOSE IN ACCORDANCE WITH  
APPLICABLE FEDERAL, STATE, PROVINCIAL, LOCAL ENVIRONMENTAL  
REGULATIONS. EMPTY CONTAINERS SHOULD BE RECYCLED OR DISPOSED OF  
THROUGH APPROVED WASTE MANAGEMENT FACILITY. PRODUCT IS  
BIODEGRADABLE IN BIOLOGICAL WASTEWATER TREATMENT PLANT.

===== MSDS Transport Information =====

T

Transport Information:U.S. D.O.T.: NON-BULK: PROPER SHIPPING NAME:  
ISOPROPANOL; UN 1219: HAZARD CLASS: 3; PKG: I I. BULK: PROPER  
SHIPPING NAME: ISOPROPANOL; UN1219; HAZARD CLASS: 3; PKG: I I.  
ADDITIONAL TRANSPORTATION SYSTEM INFORMATION CAN BE OBTAINED  
THROUGH YOUR UCC SALES OR CUSTOMER SERVICE REPRESENTATIVE.

===== Regulatory Information =====

SARA Title III Information:SECTIONS 302 AND 304: NONE OF THE COMPONENTS  
OF THIS PRODUCT ARE LISTED AS EXTREMELY HAZARDOUS SUBSTANCES IN 40  
CFR PART 355 AND ARE PRESENT AT LEVELS WHICH COULD REQUIRE  
REPORTING AND EMERGENCY PLANNING. SECTION 313: NONE OF THE  
COMPONENTS OF THIS PRODUCT ARE LISTED AS TOXIC CHEMICALS IN 40 CFR  
372.65 AND ARE PRESENT AT LEVELS WHICH COULD REQUIRE REPORTING AND  
CUSTOMER NOTIFICATION UNDER SECTION 313 AND 40 CFR PART 372.  
SECTION 311 AND 312: DELAYED HAZARD: YES; FIRE HAZARD: YES;  
IMMEDIATE HEALTH HAZARD: YES; REACTIVE HAZARD: NO; Sudden  
Release  
OF PRESSURE HAZARD: NO.

Federal Regulatory Information:CERCLA:SECTION 103: NO COMPONENTS OF  
THIS PRODUCT ARE LISTED AS HAZARDOUS SUBSTANCES IN 40 CFR 302.4  
(UNLISTED HAZARDOUS SUBSTANCES NOT IDENTIFIED) AND PRESENT AT  
LEVELS WHICH COULD REQUIRE REPORTING. TOXIC SUBSTANCES CONTROL ACT  
(TSCA):ALL COMPONENTS OF THIS PRODUCT ARE ON TSCA INVENTORY OR ARE  
EXEMPT FROM TSCA INVENTORY REQUIREMENTS.

State Regulatory Information:PENNSYLVANIA: THIS PRODUCT IS SUBJECT TO

THE WORKER AND COMMUNITY RIGHT-TO-KNOW ACT. THE FOLLOWING  
COMPONENTS OF THIS PRODUCT ARE AT LEVELS WHICH COULD REQUIRE  
IDENTIFICATION IN MSDS: ISOPROPANOL, CAS # 67-63-0,