View NSN Online: https://aerobasegroup.kr/nsn/8030-01-395-2726

Product ID: POLYSULFIDE RUBBER COMPOUND PRO SEAL 870 C-12 BASE COMPOUND MSDS Date:09/06/1994 FSC:8030 NIIN:01-395-2726 Status Code:A MSDS Number: CLQSZ === Responsible Party === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG **INDUSTRIES COMPANY** Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Info Phone Num:818-240-2060 Emergency Phone Num:800-228-5635 Preparer's Name: ERNEST CARTER Chemtrec Ind/Phone:(800)424-9300 CAGE:83574 === Contractor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574 ======== Composition/Information on Ingre dients ========== Ingred Name:TOLUENE CAS:108-88-3 RTECS #:XS5250000 = Wt:15. **OSHA PEL:SEE TABLE Z-2** ACGIH TLV:188 MG/M3:50 PPM EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: POLYSULFIDE POLYMER CAS:68611-50-7 Code:F Ingred Name: TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 = Wt:10. OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

:67762-90-7 Code:F

Effects of Overexposure: EYES: MAY CAUSE BURNING, TEARING AND REDDENING. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN, AND POSSIBLE DERMATITIS. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS AND FATIGUE. MAY C AUSE LIVER AND KIDNEY DAMAGE. INGESTION: MAY CAUSE DROWSINESS, DIZZINESS AND NAUSEA.

First Aid:EYE

S: FLUSH WITH LUKE WARM WATER FOR 15 MINUTES. CONSULT PHYSICIAN.SKIN: WASH WITH SOAP AND WATER. CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. CONSULT A PHYSICIAN. INGESTION: CONSULT A PHYS ICIAN.

Flash Point Method:SCC Flash Point:=18.3C, 65.F Lower Limits:1.2% Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER FOG. Fire Fighting Procedures: USE AIR SUPPLIED RESPIRATOR. USE WATER TO COOL HEA

T EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard: HIGH TEMPERATURE MAY CAUSE PRESSURE BUILD UP IN CLOSED CONTAINER.

Spill Release Procedures: REMOVE ALL IGNITION SOURCES. COVER WITH ABSORBENT. SCOOP INTO CONTAINERS. CLEAN UP RESIDUE WITH A SUITABLE SOLVENT.

Handling and Storage Precautions: WASH THOROUGHLY AFTER HANDLING AND **BEFORE SMOKING OR**

EATING. AVOID INGESTION. Other Precautions: EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM.

Respiratory Protection:WHEN APPLYING IN ANY CIRCUMSTANCES LIKELY TO PRODUCE AIRBORNE LEVEL OF HAZARDOUS INGREDIENTS IN EXCESS OF TLV, USE AN ORGANIC VAPOR CARTRIDGE OR AIR-SUPPLIED RESPIRATOR. Ventilation:GENERAL VENTILATION TO MAINTAIN VAPORS BELOW PEL. Protective Gloves:SOLVENT RESIS TANT GLOVES. Eye Protection:CHEMICAL GOGGLES OR FULL FACE SHIELD. Other Protective Equipment:KEEP CONTAINER TIGHTLY CLOSED. Supplemental Safety and Health

Vapor Density:HEAVIER Spec Gravity:1.43 VOC Pounds/Gallon:124 Appearance and Odor:BEIGE SEMI-LIQUID Percent Volatiles by Volume:21.7%

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS.

Ha

zardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE, TRACES OF HYDROGEN SULFIDE. Conditions to Avoid Polymerization:WILL NOT OCCUR.

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE WITH FEDERAL AND STATE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no ma

nner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.