

PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY -- POLYSULFIDE RUBBER COMPOUND PR1750 B-2 BASE COMPOUND -- 8030-00-560-8758

=====
Product Identification
=====

Product ID:POLYSULFIDE RUBBER COMPOUND PR1750 B-2 BASE COMPOUND

MSDS Date:08/19/1997

FSC:8030

NIIN:00-560-8758

Status Code:A

MSDS Number: CLRTZ

=== Responsible Party ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:(800)424-9300

Preparer's Name:HENRY SIMMONS

Chemtrec Ind/Phone:(800)424-9300

CAGE:83574

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE

CAS:1317-65-3

RTECS #:EV9580000

= Wt:30.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

< Wt:5.

OSHA PEL:15 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:TOLUENE

CAS:108-88-3

RTECS #:XS5250000

< Wt:1.

OSHA PEL:SEE TABLE Z-2

==

Reports of Carcinogenicity:NTP:UNKNOWN IARC:YES
Effects of Overexposure:TOLUENE EYES: MAY CAUSE BURNING, TEARING AND REDDENING. SKIN: PROLONGED EXPOSURE MAY CAUSE DRYING AND CRACKING OF SKIN, AND POSSIBLE DERMATITIS. INHALATION: MAY CAUSE DIZZINESS, DROWSINESS AND FATIGU E. MAY CAUSE LIVER AND KIDNEY DAMAGE. INGESTION: MAY CAUSE DROWSINESS, DIZZINESS, NAUSEA. EFFECTS OF LONG TERM EXPOSURE: DISTURBANCE IN MEMORY, THINKING ABILITY, EMOTIONS, COORDINATION.

=====

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH WARM WATER FOR 15 MINUTES. IF SYMPTOMS PERSISTS, CONSULT A PHYSICIAN. SKIN: WASH WITH SOAP AND WATER. IF SYMPTOMS PERSISTS, CONSULT A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. IF SYMPTOMS ARE PRESENT. CONSULT A PHYSICIAN. INGESTION: DRINK LARGE AMOUNTS OF WATER; INDUCE VOMITING; CONSULT A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:>
93.3C, 200.F
Lower Limits:1.1%
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM, WATER SPRAY
Fire Fighting Procedures:USE AIR SUPPLIED RESPIRATOR.
Unusual Fire/Explosion Hazard:NOT KNOWN

===== Accidental Release Measures =====

Spill Release Procedures:SCOOP INTO CONTAINERS. CLEAN-UP RESIDUE WITH A SUITABLE SOLVENT

===== Handling and Storage =====

Handling and Storage Precautions:WASH THOROUGHLY AFTER HANDLING AND B EFORE SMOKING OR EATING. AVOID INGESTION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT REQUIRED
Ventilation:GENERAL VENTILATION
Protective Gloves:SOLVENT RESISTANT GLOVES
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE KNOWN
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt.=110.C, 230.F
B.P. Text:230-482
Vapor Density:> AIR
Spec Gravity:1.571
Evaporation Rate & Re

ference:> THAN N-BUTYL ACETATE

Appearance and Odor:BEIGE THIXOTROPIC PASTE

Percent Volatiles by Volume:3.1%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NOT KNOWN

Stability Condition to Avoid:NOT KNOWN

Hazardous Decomposition Products:OXIDES OF CARBON, SULFUR DIOXIDE,
TRACES OF HYDROGEN SULFIDE

===== Disposal Considerations =====

Waste Disposal Methods:NOT A HAZARDOUS WASTE ACCORDING TO EPA
REGULATION. CONSULT STATE REGULATIONS PRIOR TO DISPOSAL OF
SPILLAGE.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document

should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.